

MURATA CMCC products
For Power line - Automotive Grade -



(inch/mm)	2A	4A	6A	8A	10A	12A	14A	16A	18A	Rated Current
3.2 x 2.5 x 2.5 max.mm (1210/3225)	1.2 ●	New ▶ DLW32PH_XK2 (-40 to +125 °C) PowerTrain/Safety								
4.0 x 4.0 x 1.5 max.mm (1515/4040)	Note: In regard to the rated current, derating may be necessary, depending on the operating temperature.									
5.0 x 3.6 x 2.4 max.mm (2014/5036)	1.5 2.0 2.5 3.0 4.0 ● ● ● ● ●	▶ DLW5ATZ_MQ2 (-40 to +105 °C) Infotainment ▶ DLW5ATZ_TQ2 (-40 to +105 °C) Infotainment ▶ DLW5ATH_MQ2 (-40 to +125 °C) PowerTrain/Safety ▶ DLW5ATH_TQ2 (-40 to +125 °C) PowerTrain/Safety								
5.0 x 3.6 x 4.3 max.mm (2014/5036)										
5.0 x 5.0 x 2.5 max.mm (2020/5050)	1.5 2.0 2.5 3.0 4.0 ● ● ● ● ●	▶ DLW5BTZ_TQ2 (-40 to +105 °C) Infotainment ▶ DLW5BTH_TQ2 (-40 to +125 °C) PowerTrain/Safety								
5.0 x 5.0 x 4.5 max.mm (2020/5050)	0.7 1.0 1.5 ● ● ●	▶ DLW5BSZ_TQ2 (-40 to +105 °C) Infotainment								
5.0 x 5.0 x 5.0 max.mm (2020/5050)			3.1 3.7 4.4 5.6 ● ● ● ●	▶ PLT5BPH (-55 to +150 °C) PowerTrain/Safety						
12.9 x 6.6 x 9.3 max.mm	▶ PLT10HH (-55 to +105 °C) PowerTrain/Safety				6.0	10.0				
	▶ PLT10HH (-55 to +125 °C) PowerTrain/Safety				6.0	10.0	15.0	18.0		